

### PRODUCTS CATALOGUE "AT EASE IN YOUR CONSTRUCTION SITE"

Bung





# **Ritmo meets all your welding needs in your jobsite**



The information and photos in this publication are not binding and RITMO S.P.A. is free to make any alterations without prior notice.

## DVANTAGE RITMO



#### **RITMO WORLDWIDE**

Ritmo has professional distributors and resellers all over the world. Our staff is ready to assist you in English, Spanish, French, German, Arab, Italian, Russian and Portuguese.

#### TRAINING

From many years now, we have decided that the best way to grant a client/ distributor a perfect knowledge of our products Is to invest in custom training, in our own premises. These courses are aimed to teach how to operate the products in the best way, and how to supply the "first aid" when necessary.

#### **PRESALES TECHNICAL ASSISTANCE**

When a client or a potential client wants to buy us a product, it is our standard procedure to help find the best solution to its needs.

#### **GLOBAL ADVICE**

In such a technical field as ours, the customer requires the best assistance. Thanks to the experience developed along the years, and to the co-operation with several manufacturers, institutions, schools and training institutes, RITMO is able to give the most comprehensive advice to no matter which related issue. Our company is a long-time member of a UNIPLAST's (UNI-Italian National Plastics Standards Body) working group dedicated to the study and draw up of new standards within our field. The importance of this group is linked to the fact that the expansion of the plastic welding field ought to be followed by a crescent sensitivity for safety issues, so to have a sustainable and continuous growth. The working group prepares draws, hence present them to the UNI to be discussed and eventually transformed into new standards.

#### AFTER SALES TECHNICAL ASSISTANCE

Ritmo's Service Centre can solve all kind of technical issues, as well as overhaul our machines. Ritmo has other Service Centres abroad, linked to its official distributors.

#### **STARTING AND TESTING**

RITMO' technicians are prepared to make the starting and testing of workshop machines at the client' own premises, so that the fittings production can start almost immediately.



## **BUTT FUSION MACHINES** LIQUID DRAINAGE



| WORKING RANGE Ø mm     | 40 | 50               | 63 | 75 | 90 | 110              | 125 | 140 | 160 | 180                               | 200 | 225 | 250 | 280 | 315  |  |
|------------------------|----|------------------|----|----|----|------------------|-----|-----|-----|-----------------------------------|-----|-----|-----|-----|------|--|
| MINI 160 JOYT          | 40 | 50               | 63 | 75 | 90 | 110              | 125 | 140 | 160 |                                   |     |     |     |     |      |  |
| MINI 160 JOYT ELBOWS   | 40 | 50               | 63 | 75 | 90 | 110              | 125 | 140 | 160 |                                   |     |     |     |     |      |  |
| VR 160 JOYT            | 40 | 50               | 63 | 75 | 90 | 110              | 125 | 140 | 160 |                                   |     |     |     |     |      |  |
| VR 250                 |    |                  |    | 75 | 90 | 110              | 125 | 140 | 160 | 180                               | 200 | 225 | 250 |     |      |  |
| MAXI 315               |    |                  |    |    | 90 | 110              | 125 | 140 | 160 | 180                               | 200 | 225 | 250 | 280 | 315  |  |
| WORKING RANGE Ø mm     | 40 | 50               | 63 | 75 | 90 | 110              | 125 | 140 | 160 | 180                               | 200 | 225 | 250 | 280 | 315  |  |
|                        |    |                  |    |    |    |                  |     |     |     |                                   |     |     |     |     |      |  |
| WORKING RANGE Ø mm / i | n  | 110 mm / 3" DIPS |    |    |    | 125 mm / 4" DIPS |     |     | 1   | 180 mm / 6" DIPS 280 mm / 10" DIP |     |     |     |     | DIPS |  |
| TP 125 /45°            |    | •                |    |    |    |                  |     |     |     |                                   |     |     |     |     |      |  |
| TP 125                 |    | •                |    |    |    | •                |     |     |     |                                   |     |     |     |     |      |  |
| TP 200                 |    | •                |    |    |    | •                |     |     |     |                                   | •   |     |     |     |      |  |
| TP 300                 |    | •                |    |    |    | •                |     |     |     | •                                 |     |     |     | •   |      |  |



## **MAXI 315**

A professional welding machine ideal for medium sized pipes and sewers up to Ø 315 mm. It consists of a machine body with pressure regulating device, a pair of clamps, two lateral supports, an electrically controlled milling cutter for levelling the ends of the pipe and/or fitting with a safety microswitch, an extractable heating plate with automatic electronic device to control the temperature, a sliding support, a tip-up metal frame on wheels that acts as a work bench and protection when transporting the machine. The MAXI 315 can weld fittings such as bends and tees. Branches can also be welded thanks to the single clamps (available on request) indicated for all diameters in the working range.

#### **STANDARD COMPOSITION**

- Machine body with a milling cutter and lateral supports
- TP 315 TE plate
- Right and Left clamp Ø 315
- Steel frame on wheels (for transporting and for use as a work bench)
- Wooden case with clamps and lateral supports adapters Ø 200 and 250 mm

#### **ON REQUEST**

- Clamp adapters Ø 90, 110, 125, 140, 160, 180, 225, 280 mm
- Lateral supports adapters Ø 90, 110, 125, 140, 160, 180, 225, 280 mm



#### **TECHNICAL FEATURES**

| Working range                     | 90 ÷ 315 mm                 |  |  |  |  |
|-----------------------------------|-----------------------------|--|--|--|--|
| Materials                         | HDPE, PP, PB, PVDF          |  |  |  |  |
| Power supply                      | 230 V Single Phase 50/60 Hz |  |  |  |  |
| Max. absorbed power               | 3900 W                      |  |  |  |  |
| Working temperature               | 180° ÷ 280° C               |  |  |  |  |
| Outside temperature range         | -5° ÷ 40° C                 |  |  |  |  |
| Time to reach welding temperature | ~ 20'                       |  |  |  |  |
| Weight                            | 183 Kg                      |  |  |  |  |
| Dimensions machine working        | 1420 x 1300 x 1570 mm       |  |  |  |  |















www.ritmo.it

**RITMO S.p.A.** Via A. Volta, 35/37 - 35037 Bresseo di Teolo (PADOVA) ITALY

Ph. +39 049 9901888 Fax +39 049 9901993

> info@ritmo.it www.ritmo.it

