

# PRODUCTS CATALOGUE

"AT EASE IN YOUR CONSTRUCTION SITE"

[www.ritmo.it](http://www.ritmo.it) 





# Ritmo meets all your welding needs in your jobsite



The information and photos in this publication are not binding and RITMO S.P.A. is free to make any alterations without prior notice.



# A DVANTAGE

## RITMO



### **RITMO WORLDWIDE**

Ritmo has professional distributors and resellers all over the world. Our staff is ready to assist you in English, Spanish, French, German, Arab, Italian, Russian and Portuguese.

### **TRAINING**

From many years now, we have decided that the best way to grant a client/distributor a perfect knowledge of our products is to invest in custom training, in our own premises. These courses are aimed to teach how to operate the products in the best way, and how to supply the "first aid" when necessary.

### **PRESALES TECHNICAL ASSISTANCE**

When a client or a potential client wants to buy us a product, it is our standard procedure to help find the best solution to its needs.

### **GLOBAL ADVICE**

In such a technical field as ours, the customer requires the best assistance. Thanks to the experience developed along the years, and to the co-operation with several manufacturers, institutions, schools and training institutes, RITMO is able to give the most comprehensive advice to no matter which related issue. Our company is a long-time member of a UNIPLAST's (UNI-Italian National Plastics Standards Body) working group dedicated to the study and draw up of new standards within our field. The importance of this group is linked to the fact that the expansion of the plastic welding field ought to be followed by a crescent sensitivity for safety issues, so to have a sustainable and continuous growth. The working group prepares draws, hence present them to the UNI to be discussed and eventually transformed into new standards.

### **AFTER SALES TECHNICAL ASSISTANCE**

Ritmo's Service Centre can solve all kind of technical issues, as well as overhaul our machines. Ritmo has other Service Centres abroad, linked to its official distributors.

### **STARTING AND TESTING**

RITMO' technicians are prepared to make the starting and testing of workshop machines at the client' own premises, so that the fittings production can start almost immediately.

# RITMO'S BUTT FUSION MACHINES: WORK PHILOSOPHY AVAILABLE TO EVERYONE!

## - **MANUAL**

welding machines without hydraulic gearcase



## - **HYDRAULIC**

welding machines with hydraulic gearcase



## - **EASY LIFE SYSTEM** *HIGH LEVEL PERFORMANCE*

automated welding cycle


welding machines with special hydraulic gearcase

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF,

APP "SET & GO PRO" (optional)



## - **ALL TERRAIN** *HIGH LEVEL PERFORMANCE*

self-contained generator on board

self-propelled

trolley with wheels

welding machines with special hydraulic gearcase

automated welding cycle

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF,

APP "SET & GO PRO" (optional)



## - **CNC** *HIGH LEVEL PERFORMANCE*

automatic welding cycle

special hydraulic gearcase and machine body with

integrated mechanical extraction of heating plate

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF





## DELTA 1000

This is a self-aligning machine, suitable for welding ducts for the transport of water and other fluids under pressure, up to  $\varnothing$  1000 mm - 36" IPS. The DELTA 1000 was designed in accordance to the International correspondent standards (UNI 10565, ISO 12176-1), and consists of:

- Machine body with a bearing frame, four steel clamps and two hydraulic thrust cylinders with non-drip quick couplings and steel inserts.
- Extractable heating plate with separate thermometer for reading the working temperature.
- Extractable electrically controlled milling cutter (with self detaching device) for levelling the ends of the pipe and/or fitting, with a safety microswitch, overload cut out, and emergency push button.
- Electrohydraulic gearcase with a clamp opening and closing lever, maximum pressure and discharge valves (useful also during the "Dual Pressure" welding), hydraulic hoses with non-drip quick couplings, a timer (for the heating and welding phases) and an electrical panel with a differential circuit breaker.
- Milling cutter/heating plate support with an electronic thermoregulator for the control of the working temperatures.

Holes on the chassis to hook the machine for a rapid and easier handling.

DELTA 1000 can weld fittings such as bends, tees, branches and flange necks. This is possible because the 3rd clamp can be anchored to the 1st and 2nd (movable) and slide along with the pipe. The fitting must be locked in the 4th clamp. Necks with a highly reduced tang can be welded with the help of a special tool (on request), applied to the clamps.

### STANDARD COMPOSITION



Machine body



Detach device for heater




Gearcase



Electronic thermoregulator



Milling cutter



Heating plate



Support



## TECHNICAL FEATURES

**PLUS**

630 ÷ 1000 mm

**HOLE FOR RAPID  
AND EASIER  
HANDLING**

\* Suggested power generator  
40kVA

|                                     |   |
|-------------------------------------|---|
| Working range                       | 630 ÷ 1000 mm;<br>24" IPS ÷ 36" IPS                   |
| Materials                           | HDPE, PP,<br>For other materials contact RITMO S.P.A. |
| Power supply*                       | 400 V 3F+N+PE 50/60 HZ                                |
| Total absorbed power                | 25000 W   |
| Working temperature                 | 180° ÷ 280° C (356° ÷ 536° F)                         |
| Outside temperature range           | -10° ÷ 40° C (14° ÷ 104° F)                           |
| Time to reach welding temperature   | < 45'   |
| Dimensions machine body (W x D x H) | 2386 x 1746 x 1711 mm<br>(94" x 69" x 67")            |
| Weight machine body                 | 2090 Kg (4607 lb)                                     |
| Weight standard composition         | 2942 Kg (6486 lb)                                     |

### ON REQUEST



Inserts  
Ø 630 ÷ 900 mm



Tool for flange  
necks



Trolley



Electrical crane



The INSPECTOR  
Data-logging



Rollers

and:  
Inserts Ø 24" ÷ 36" IPS

Oman



# BUTT FUSION MACHINES REFERENCE



| WORKING RANGE Ø mm        | 32 | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 | 710 | 800 | 900 | 1000 | 1200 | 1400 | 1600 |      |  |
|---------------------------|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|------|------|------|------|------|--|
| GAMMA 160                 |    | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| DELTA 160 M               | 32 | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| DELTA 200 M               |    |    |    | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 |     |     |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| BASIC 160                 |    | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| BASIC 200                 |    |    |    | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 |     |     |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| BASIC 250                 |    |    |    |    | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| BASIC 315                 |    |    |    |    |    | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| BASIC 355                 |    |    |    |    |    |    |     | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| COMPACT 355               |    |    |    |    |    |    |     | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| BASIC 160 EASY LIFE       |    | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| BASIC 200 EASY LIFE       |    |    |    | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 |     |     |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| BASIC 250 EASY LIFE       |    |    |    |    | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| BASIC 315 EASY LIFE       |    |    |    |    |    | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| BASIC 355 EASY LIFE       |    |    |    |    |    |    |     | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| DELTA 500 EASY LIFE       |    |    |    |    |    |    |     |     |     |     |     | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 |     |     |     |     |     |      |      |      |      |      |  |
| DELTA 630 EASY LIFE       |    |    |    |    |    |    |     |     |     |     |     |     |     |     | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 |     |     |     |      |      |      |      |      |  |
| DELTA 500                 |    |    |    |    |    |    |     |     |     |     |     | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 |     |     |     |     |     |      |      |      |      |      |  |
| DELTA 630                 |    |    |    |    |    |    |     |     |     |     |     |     |     |     | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 |     |     |     |      |      |      |      |      |  |
| DELTA 800                 |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     | 500 | 560 | 630 | 710 | 800 |      |      |      |      |      |  |
| DELTA 1000                |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | 630 | 710 | 800 | 900  | 1000 |      |      |      |  |
| DELTA 1200                |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | 710 | 800 | 900  | 1000 | 1200 |      |      |  |
| DELTA 1600 ECO / 1600 HDR |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     | 800 | 900  | 1000 | 1200 | 1400 | 1600 |  |
| DELTA 250 TRAILER         |    |    |    |    | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| DELTA 355 TRAILER         |    |    |    |    |    |    |     | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| DELTA 355 ALL TERRAIN     |    |    |    |    |    |    |     | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| DELTA 500 TRAILER         |    |    |    |    |    |    |     |     |     |     |     | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 |     |     |     |     |     |      |      |      |      |      |  |
| DELTA 500 ALL TERRAIN     |    |    |    |    |    |    |     |     |     |     |     | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 |     |     |     |     |     |      |      |      |      |      |  |
| DELTA 630 TRAILER         |    |    |    |    |    |    |     |     |     |     |     |     | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 |     |     |     |      |      |      |      |      |  |
| DELTA 630 ALL TERRAIN     |    |    |    |    |    |    |     |     |     |     |     |     | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 |     |     |     |      |      |      |      |      |  |
| DELTA 1000 TRAILER        |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     | 315 | 355 | 400 | 450 | 500 | 560 | 630 | 710 | 800 | 900 | 1000 |      |      |      |      |  |
| DELTA DRAGON 250 CNC      |    |    |    |    | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 |     |     |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| DELTA DRAGON 315 CNC      |    |    |    |    |    | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 |     |     |     |     |     |     |     |     |     |      |      |      |      |      |  |
| WORKING RANGE Ø mm        | 32 | 40 | 50 | 63 | 75 | 90 | 110 | 125 | 140 | 160 | 180 | 200 | 225 | 250 | 280 | 315 | 355 | 400 | 450 | 500 | 560 | 630 | 710 | 800 | 900 | 1000 | 1200 | 1400 | 1600 |      |  |

| CTS                       | IPS |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
|---------------------------|-----|-----|-----|----|----|-----|-----|----|----|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|---|---|---|---|---|---|--|--|--|--|
|                           | 1"  | 1¼" | 1½" | 2" | 1" | 1¼" | 1½" | 2" | 3" | 4" | 5" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 22" | 24" | 26" | 28" | 30" | 32" | 34" | 36" | 42" | 48" | 52" | 54" | 63" |   |   |   |   |   |   |  |  |  |  |
| GAMMA 160                 |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 160 M               | •   | •   | •   | •  | •  | •   | •   | •  | •  | •  | •  | •  | •  | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | • | • | • |   |   |   |  |  |  |  |
| DELTA 200 M               |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| BASIC 160                 |     |     |     |    | •  | •   | •   | •  | •  | •  | •  | •  | •  | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | • | • | • | • |   |   |  |  |  |  |
| BASIC 200                 |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| BASIC 250                 |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| BASIC 315                 |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| BASIC 355                 |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| COMPACT 355               |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| BASIC 160 EASY LIFE       |     |     |     |    | •  | •   | •   | •  | •  | •  | •  | •  | •  | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | •   | • | • | • | • | • | • |  |  |  |  |
| BASIC 200 EASY LIFE       |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| BASIC 250 EASY LIFE       |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| BASIC 315 EASY LIFE       |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| BASIC 355 EASY LIFE       |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 500 EASY LIFE       |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 630 EASY LIFE       |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 500                 |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 630                 |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 800                 |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 1000                |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 48"                 |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 1600 ECO / 1600 HDR |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA TRAILER 250         |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 355 TRAILER         |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 355 ALL TERRAIN     |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 500 TRAILER         |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 500 ALL TERRAIN     |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 630 TRAILER         |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 630 ALL TERRAIN     |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| DELTA 1000 TRAILER        |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |
| IPS                       |     |     |     |    |    |     |     |    |    |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |   |   |   |   |   |   |  |  |  |  |

| DIPS                      |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
|---------------------------|----|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|
|                           | 3" | 4" | 6" | 8" | 10" | 12" | 14" | 16" | 18" | 20" | 24" | 30" | 36" | 42" | 48" | 54" | 60" |  |
| GAMMA 160                 |    | •  |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 160 M               | •  | •  |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 200 M               | •  | •  | •  |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| BASIC 160                 | •  | •  |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| BASIC 200                 | •  | •  | •  |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| BASIC 250                 | •  | •  | •  | •  |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| BASIC 315                 | •  | •  | •  | •  | •   |     |     |     |     |     |     |     |     |     |     |     |     |  |
| BASIC 355                 | •  | •  | •  | •  | •   | •   |     |     |     |     |     |     |     |     |     |     |     |  |
| COMPACT 355               | •  | •  | •  | •  | •   | •   | •   |     |     |     |     |     |     |     |     |     |     |  |
| BASIC 160 EASY LIFE       | •  | •  |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| BASIC 200 EASY LIFE       | •  | •  | •  |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| BASIC 250 EASY LIFE       | •  | •  | •  | •  |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| BASIC 315 EASY LIFE       | •  | •  | •  | •  | •   |     |     |     |     |     |     |     |     |     |     |     |     |  |
| BASIC 355 EASY LIFE       | •  | •  | •  | •  | •   | •   |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 500 EASY LIFE       |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 630 EASY LIFE       |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 500                 |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 630                 |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 800                 |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 48"                 |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 1600 ECO / 1600 HDR |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA TRAILER 250         | •  | •  | •  | •  |     |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 355 TRAILER         | •  | •  | •  | •  | •   |     |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 355 ALL TERRAIN     | •  | •  | •  | •  | •   | •   |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 500 TRAILER         | •  | •  | •  | •  | •   | •   |     |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 500 ALL TERRAIN     | •  | •  | •  | •  | •   | •   | •   |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 630 TRAILER         | •  | •  | •  | •  | •   | •   | •   |     |     |     |     |     |     |     |     |     |     |  |
| DELTA 630 ALL TERRAIN     | •  | •  | •  | •  | •   | •   | •   | •   |     |     |     |     |     |     |     |     |     |  |
| DELTA 1000 TRAILER        | •  | •  | •  | •  | •   | •   | •   | •   |     |     |     |     |     |     |     |     |     |  |
| DIPS                      |    |    |    |    |     |     |     |     |     |     |     |     |     |     |     |     |     |  |







**Ritmo**  
PLASTIC WELDING TECHNOLOGY





The information and photos in this publication are not binding and RITMO S.P.A. is free to make any alterations without prior notice.



**RITMO S.p.A.**

Via A. Volta, 35/37 - 35037  
Bresseo di Teolo (PADOVA) ITALY

Ph. +39 049 9901888  
Fax +39 049 9901993

[info@ritmo.it](mailto:info@ritmo.it)  
[www.ritmo.it](http://www.ritmo.it)

