

PRODUCTS CATALOGUE

"AT EASE IN YOUR CONSTRUCTION SITE"

www.ritmo.it





Ritmo meets all your welding needs in your jobsite



The information and photos in this publication are not binding and RITMO S.P.A. is free to make any alterations without prior notice.

A DVANTAGE

RITMO



RITMO WORLDWIDE

Ritmo has professional distributors and resellers all over the world. Our staff is ready to assist you in English, Spanish, French, German, Arab, Italian, Russian and Portuguese.

TRAINING

From many years now, we have decided that the best way to grant a client/distributor a perfect knowledge of our products is to invest in custom training, in our own premises. These courses are aimed to teach how to operate the products in the best way, and how to supply the “first aid” when necessary.

PRESALES TECHNICAL ASSISTANCE

When a client or a potential client wants to buy us a product, it is our standard procedure to help find the best solution to its needs.

GLOBAL ADVICE

In such a technical field as ours, the customer requires the best assistance. Thanks to the experience developed along the years, and to the co-operation with several manufacturers, institutions, schools and training institutes, RITMO is able to give the most comprehensive advice to no matter which related issue. Our company is a long-time member of a UNIPLAST's (UNI-Italian National Plastics Standards Body) working group dedicated to the study and draw up of new standards within our field. The importance of this group is linked to the fact that the expansion of the plastic welding field ought to be followed by a crescent sensitivity for safety issues, so to have a sustainable and continuous growth. The working group prepares draws, hence present them to the UNI to be discussed and eventually transformed into new standards.

AFTER SALES TECHNICAL ASSISTANCE

Ritmo's Service Centre can solve all kind of technical issues, as well as overhaul our machines. Ritmo has other Service Centres abroad, linked to its official distributors.


STARTING AND TESTING

RITMO' technicians are prepared to make the starting and testing of workshop machines at the client' own premises, so that the fittings production can start almost immediately.

RITMO'S BUTT FUSION MACHINES: WORK PHILOSOPHY AVAILABLE TO EVERYONE!

- **MANUAL**

welding machines without hydraulic gearcase



- **HYDRAULIC**

welding machines with hydraulic gearcase



- **EASY LIFE SYSTEM** *HIGH LEVEL PERFORMANCE*

automated welding cycle


welding machines with special hydraulic gearcase

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF,

APP "SET & GO PRO" (optional)



- **ALL TERRAIN** *HIGH LEVEL PERFORMANCE*

self-contained generator on board

self-propelled

trolley with wheels

welding machines with special hydraulic gearcase

automated welding cycle

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF,

APP "SET & GO PRO" (optional)



- **CNC** *HIGH LEVEL PERFORMANCE*

automatic welding cycle

special hydraulic gearcase and machine body with

integrated mechanical extraction of heating plate

Hardware and Software interact to the entire workflow

repetition of welding cycles

GPS, data-logging and report PDF





BASIC 315

Self-aligning hydraulic butt fusion machines, suitable for welding under-pressure pipes for water, gas and other fluids. Built according to the International standards (UNI 10565, ISO 12176-1), BASIC 315 includes:

- A machine body built with a supporting frame, four clamps and two hydraulic cylinders with fast non-drip coupling connections. It comes with the fast-locking-adapters system SMARTLock patented by Ritmo
- A Teflon-coated (PTFE) heating plate with a built-in independent thermometer, to check the working temperature, and an high-precision electronic thermoregulator "Digital Dragon" ($\pm 1^{\circ}\text{C}$) with digital display and regulating buttons. This system includes Led indicators to check if the machine is working normally (live tension and working temperature), contingent probe's failures and/or temperature anomalies.
- An extractable electric milling cutter to face the heads of the pipes and/or fittings. It includes a safety micro-switch and a thermal circuit breaker.
- An electro-hydraulic gearcase protected from crashes and atmospheric corrosion by a plastic box. It includes a control lever, to open and close the clamps, maximum pressure and discharge valves (useful also for the "Dual Pressure" welding process), hydraulic connection hoses with non-drip fast couplings and timer (to check the warming and welding time). The machine is preset for the connection of the electronic controller THE INSPECTOR.
- A milling cutter/ heating plate support

BASIC 315 is able to weld fittings like elbows, tees, Y-branches and flanges necks.
Available in the 110 V and 230 V versions.

STANDARD COMPOSITION



Machine body



Detach device
for heater



Gearcase



Heating plate
with Digital
Dragon



Milling cutter



Support

TECHNICAL FEATURES

PLUS

SMARTLOCK
PATENTED BY RITMO
fast-locking
adapters system

DIGITAL DRAGON
High-Precision
Electronic
Thermoregulator

* Suggested power generator
6,5 ÷ 7kVA

Working range	90 ÷ 315 mm; 3" IPS ÷ 10" DIPS
Materials	HDPE, PP, PP-R, PVDF For other materials contact RITMO S.P.A.
Power supply*	110 V Single Phase 50/60 Hz 230 V Single Phase 50/60 Hz
Total absorbed power	3900 W (110 V) 4500W (230 V)
Working temperature	180° ÷ 280° C (356° ÷ 536° F)
Outside temperature range	-10° ÷ 40° C (14° ÷ 104° F)
Time to reach welding temperature	< 20'
Dimensions machine body (W x D x H)	981 x 586 x 520 mm (37" x 23" x 20.5")
Weight machine body	86 Kg (190 lb)
Weight standard composition	166 Kg (366 lb)

ON REQUEST



Inserts
Ø 90 ÷ 280 mm
master Ø 250 mm



Tool for flange
necks



Trolley for
machine body



The INSPECTOR
Data-logging



Rollers



watch the video

and:

Inserts Ø 3" ÷ 10" IPS; 3" ÷ 10" DIPS

pre-insulated bag for heating plate, trolley for milling cutter/heating plate, wooden case for inserts

Italy



BUTT FUSION MACHINES REFERENCE



WORKING RANGE Ø mm	32	40	50	63	75	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	710	800	900	1000	1200	1400	1600	
GAMMA 160		40	50	63	75	90	110	125	140	160																				
DELTA 160 M	32	40	50	63	75	90	110	125	140	160																				
DELTA 200 M				63	75	90	110	125	140	160	180	200																		
BASIC 160		40	50	63	75	90	110	125	140	160																				
BASIC 200				63	75	90	110	125	140	160	180	200																		
BASIC 250					75	90	110	125	140	160	180	200	225	250																
BASIC 315						90	110	125	140	160	180	200	225	250	280	315														
BASIC 355								125	140	160	180	200	225	250	280	315	355													
COMPACT 355								125	140	160	180	200	225	250	280	315	355													
BASIC 160 EASY LIFE		40	50	63	75	90	110	125	140	160																				
BASIC 200 EASY LIFE				63	75	90	110	125	140	160	180	200																		
BASIC 250 EASY LIFE					75	90	110	125	140	160	180	200	225	250																
BASIC 315 EASY LIFE						90	110	125	140	160	180	200	225	250	280	315														
BASIC 355 EASY LIFE								125	140	160	180	200	225	250	280	315	355													
DELTA 500 EASY LIFE												200	225	250	280	315	355	400	450	500										
DELTA 630 EASY LIFE															280	315	355	400	450	500	560	630								
DELTA 500												200	225	250	280	315	355	400	450	500										
DELTA 630															280	315	355	400	450	500	560	630								
DELTA 800																				500	560	630	710	800						
DELTA 1000																						630	710	800	900	1000				
DELTA 1200																							710	800	900	1000	1200			
DELTA 1600 ECO / 1600 HDR																								800	900	1000	1200	1400	1600	
DELTA 250 TRAILER					75	90	110	125	140	160	180	200	225	250																
DELTA 355 TRAILER								125	140	160	180	200	225	250	280	315	355													
DELTA 355 ALL TERRAIN								125	140	160	180	200	225	250	280	315	355													
DELTA 500 TRAILER												200	225	250	280	315	355	400	450	500										
DELTA 500 ALL TERRAIN												200	225	250	280	315	355	400	450	500										
DELTA 630 TRAILER													225	250	280	315	355	400	450	500	560	630								
DELTA 630 ALL TERRAIN													225	250	280	315	355	400	450	500	560	630								
DELTA 1000 TRAILER																315	355	400	450	500	560	630	710	800	900	1000				
DELTA DRAGON 250 CNC					75	90	110	125	140	160	180	200	225	250																
DELTA DRAGON 315 CNC						90	110	125	140	160	180	200	225	250	280	315														
WORKING RANGE Ø mm	32	40	50	63	75	90	110	125	140	160	180	200	225	250	280	315	355	400	450	500	560	630	710	800	900	1000	1200	1400	1600	

CTS	IPS																																					
	1"	1¼"	1½"	2"	1"	1¼"	1½"	2"	3"	4"	5"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	42"	48"	52"	54"	63"						
GAMMA 160																																						
DELTA 160 M	•	•	•	•	•	•	•	•	•	•	•	•	•																									
DELTA 200 M																																						
BASIC 160					•	•	•	•	•	•	•	•	•	•																								
BASIC 200																																						
BASIC 250																																						
BASIC 315																																						
BASIC 355																																						
COMPACT 355																																						
BASIC 160 EASY LIFE					•	•	•	•	•	•	•	•	•	•																								
BASIC 200 EASY LIFE																																						
BASIC 250 EASY LIFE																																						
BASIC 315 EASY LIFE																																						
BASIC 355 EASY LIFE																																						
DELTA 500 EASY LIFE																																						
DELTA 630 EASY LIFE																																						
DELTA 500																																						
DELTA 630																																						
DELTA 800																																						
DELTA 1000																																						
DELTA 48"																																						
DELTA 1600 ECO / 1600 HDR																																						
DELTA TRAILER 250																																						
DELTA 355 TRAILER																																						
DELTA 355 ALL TERRAIN																																						
DELTA 500 TRAILER																																						
DELTA 500 ALL TERRAIN																																						
DELTA 630 TRAILER																																						
DELTA 630 ALL TERRAIN																																						
DELTA 1000 TRAILER																																						
IPS	1"	1¼"	1½"	2"	1"	1¼"	1½"	2"	3"	4"	5"	6"	8"	10"	12"	14"	16"	18"	20"	22"	24"	26"	28"	30"	32"	34"	36"	42"	48"	52"	54"	63"						

DIPS																		
	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	24"	30"	36"	42"	48"	54"	60"	
GAMMA 160																		
DELTA 160 M	•	•																
DELTA 200 M	•	•	•															
BASIC 160	•	•																
BASIC 200	•	•	•															
BASIC 250	•	•	•	•														
BASIC 315	•	•	•	•	•													
BASIC 355	•	•	•	•	•	•												
COMPACT 355	•	•	•	•	•	•	•											
BASIC 160 EASY LIFE	•	•																
BASIC 200 EASY LIFE	•	•	•															
BASIC 250 EASY LIFE	•	•	•	•														
BASIC 315 EASY LIFE	•	•	•	•	•													
BASIC 355 EASY LIFE	•	•	•	•	•	•												
DELTA 500 EASY LIFE																		
DELTA 630 EASY LIFE																		
DELTA 500																		
DELTA 630																		
DELTA 800																		
DELTA 48"																		
DELTA 1600 ECO / 1600 HDR																		
DELTA TRAILER 250	•	•	•	•														
DELTA 355 TRAILER	•	•	•	•	•													
DELTA 355 ALL TERRAIN	•	•	•	•	•	•												
DELTA 500 TRAILER	•	•	•	•	•	•	•											
DELTA 500 ALL TERRAIN	•	•	•	•	•	•	•	•										
DELTA 630 TRAILER	•	•	•	•	•	•	•	•										
DELTA 630 ALL TERRAIN	•	•	•	•	•	•	•	•	•									
DELTA 1000 TRAILER	•	•	•	•	•	•	•	•	•									
DIPS	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	24"	30"	36"	42"	48"	54"	60"	





**Ritmo**
PLASTIC WELDING TECHNOLOGY



The information and photos in this publication are not binding and RITMO S.P.A. is free to make any alterations without prior notice.



RITMO S.p.A.

Via A. Volta, 35/37 - 35037
Bresseo di Teolo (PADOVA) ITALY

Ph. +39 049 9901888
Fax +39 049 9901993

info@ritmo.it
www.ritmo.it

